

HELAIAN DATA KESELAMATAN

SAFETY DATA SHEET

Tarikh dikeluarkan: 15.03.2021 Tarikh disemak: 01.11.2023 Rujukan SDS: 040109A GHS_DWI Versi:5.0
Date of Issue: 15.03.2021 Revision date: 01.11.2023 SDS Reference: 040109A GHS_DWI Version: 5.0

SEKSYEN 1: Pengenalan bahan kimia dan pembekal

Identification of the hazardous chemical and of the supplier

1.1 Pengenalpastian produk

Product identifiers

Bentuk Produk : Gas campuran
Product Form Gas mixture
Nama Produk : n-Heksana ($\leq 1\%$), n-Pentana ($\leq 1\%$), Iso-pentana ($\leq 1\%$), Neo-pentana ($\leq 1\%$), n-Butana ($\leq 10\%$), Iso-butana ($\leq 10\%$), Nitrogen ($\leq 3\%$), Propana ($\leq 5\%$), Karbon dioksida ($< 99.9\%$), Etana ($\leq 10\%$) berbaki Metana
Product Name n-Hexane ($\leq 1\%$), n-Pentane ($\leq 1\%$), Iso-pentane ($\leq 1\%$), Neo-pentane ($\leq 1\%$), n-Butane ($\leq 10\%$), Iso-butane ($\leq 10\%$), Nitrogen ($\leq 3\%$), Propane ($\leq 5\%$), Carbon dioxide ($< 99.9\%$), Ethane ($\leq 10\%$) in Methane Balance

1.2 Cara pengenalpastian lain

Other means of identification

Tiada data tersedia
No data available

1.3 Penggunaan bahan kimia dan sekatan penggunaan yang disyorkan

Recommended use of the chemical and restrictions on use

Untuk kegunaan perindustrian sahaja, gas penentukuran. Guna seperti yang diarahkan.
Industrial and Specialty Gas Applications. Use as directed.

1.4 Butir-butir mengenai pembekal

Details of the supplier of the safety data sheet

Syarikat : CHROMA GAS SDN BHD
Company NO.178 JALAN P/AM 2, PERINDUSTRIAN ARAB MALAYSIAN PARK
71800 NILAI, NEGERI SEMBILAN
Nombor Telefon : +6012-712 5188 / +012-496 0688
Telephone number

1.5 Nombor panggilan kecemasan

Emergency telephone number

Panggilan kecemasan : +6012-712 5188 / 999
Emergency contact

SEKSYEN 2: Pengenalan bahaya

Hazards Identification

2.1 Klasifikasi bahan kimia berbahaya *Classification of the substance or mixture*

Pengelasan berlandaskan GHS-MY

Gas mudah terbakar 1	H220
<i>Flam. Gas 1</i>	<i>H220</i>
Gas mampat	H280
<i>Compressed Gas</i>	<i>H280</i>

2.2 Unsur label *Elements label*

GHS -MY Labelling

Hazard pictograms (GHS-MY) :



Satu perkataan (GHS-MY)	:	Bahaya
<i>Signal word (GHS-MY)</i>		<i>Danger</i>
Pernyataan bahaya (GHS-MY)	:	H220 – Gas mudah terbakar <i>H220 – EXTREMELY FLAMMABLE GAS</i>
<i>Hazard statements (GHS-MY)</i>		H280 - Mengandungi gas di bawah tekanan; boleh meletup jika dipanaskan. <i>H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED</i> H332 - Merbahaya jika tersedut <i>H332- Harmful if inhaled.</i> OSHA-H01 - Boleh menggantikan oksigen dan menyebabkan kelemahan pantas. <i>OSHA-H01 - May displace oxygen and cause rapid suffocation.</i> <i>CGA-HG04- MAY FORM EXPLOSIVE MIXTURES WITH AIR</i> <i>CGA-HG03- MAY INCREASE RESPIRATION AND HEART RATE</i>
Pernyataan pencegahan (GHS-MY)	:	P202 - Jangan kendalikan bahan sehingga semua langkah berjaga-jaga keselamatan telah dibaca dan difahami. <i>P202 - Do not handle until all safety precautions have been read and understood.</i> P210- Jauhkan dari panas, api terbuka, percikan api, permukaan panas. -Dilarang merokok. <i>P210- Keep away from heat, open flames, sparks, hot surfaces. -No smoking.</i> P260- Jangan sedut habuk/wasap/gas /kabus/wap/semburan <i>P260- Avoid breathing gas, vapors.</i> P271+P403 - Gunakan hanya di luar bangunan atau di dalam kawasan yang dialihudarkan dengan baik. Simpan di tempat yang dialihudarkan dengan baik. <i>P271+P403- Use and store only outdoors or in a well-ventilated place.</i> P280 – Pakai pelindung mata, pelindung wajah, sarung tangan pelindung, pakaian pelindung. <i>P280- Wear eye protection, face protection, protective gloves, protective clothing.</i> CGA-PG02 - Lindungi daripada cahaya matahari apabila suhu ambient melebihi 52°C (125°F).

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C/125°F
 CGA-PG05 - Gunakan alat pencegahan aliran balik pada paip
 CGA-PG05 - Use a back flow preventive device in the piping
 CGA-PG06 - Tutup valve selepas menggunakannya.
 CGA-PG06 - Close valve after each use and when empty
 CGA-PG10 - Gunakan hanya peralatan diberi nilai tekanan silinder
 CGA-PG10 - Use only with equipment rated for cylinder pressure
 CGA-PG21 – Buka injap silinder perlahan-lahan
 CGA-PG21 - Open valve slowly

SEKSYEN 3: Komposisi dan maklumat mengenai ramuan bahan kimia berbahaya
Composition and information on the ingredients

3.1 Bahan- bahan
Substance

Nama <i>Name</i>	Nombor CAS <i>CAS Number</i>	%	Pernyataan Bahaya <i>Hazard statement</i>
Metana <i>Methane</i>	(CAS No)74-82-8	Baki <i>Balance</i>	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i>
Etana <i>Ethane</i>	(CAS No)74-84-0	≤10	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i>
Propana <i>Propane</i>	(CAS No)74-98-6	≤5	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i>
Karbon dioksida <i>Carbon dioxide</i>	(CAS No)124-38-9	<99.9	Gas cecair H280 <i>Liquefied gas H280</i>
Nitrogen <i>Nitrogen</i>	(CAS No)7727-37-9	≤3	Gas bertekanan, H280 <i>Press. Gas, H280</i>
Iso-butana <i>Iso-butane</i>	(CAS No)75-28-5	≤10	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i>
n-Butana <i>n-Butane</i>	(CAS No)106-97-8	≤10	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i>
Iso-pentana <i>Iso-pentane</i>	(CAS No)78-78-4	≤1	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Comp.), H280</i> Carcinogenicity, Category 1A H350 Germ cell mutagenicity, Category 1B H340
n-Pentana <i>n-Pentane</i>	(CAS No)109-66-0	≤1	<i>Flam. Liq, H225</i> <i>Asp.Tox, H304</i> <i>STOT SE, H336</i> <i>Aquatic Chronic, H411</i>

Neo-pentana <i>Neo-pentane</i>	(CAS No) 463-82-1	≤1	Gas mudah terbakar, H220 <i>Flam. Gas 1, H220</i> Gas bertekanan, H280 <i>Press. Gas (Liq.), H280</i> <i>Aquatic Chronic, H411</i>
n-Heksana <i>n-Hexane</i>	(CAS No) 110-54-3	≤1	<i>Flam. Liq. 2 H225</i> <i>Asp. Tox, H304</i> <i>STOT SE, H336</i> <i>Aquatic Chronic, H411</i>

SEKSYEN 4: Langkah-langkah pertolongan cemas

First aid measures

4.1 Penerangan mengenai langkah pertolongan cemas

Description of first aid measures

- Pertolongan cemas selepas sedutan
First-aid measures after inhalation : JIKA TERSEDUT: Pindahkan mangsa kawasan berudara segar dan biarkan mangsa dalam keadaan rehat supaya mangsa dapat bernafas dengan selesa. Hubungi doctor/pakar perubatan jika anda rasa tidak sihat.
If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.
- Pertolongan cemas selepas sentuhan kulit
First-aid measures after skin contact : Kesan buruk tidak dijangka dari produk ini.
Adverse effects not expected from this product.
- Pertolongan cemas selepas sentuhan mata
First-aid measures after eye contact : Segera bilas mata dengan air sekurang-kurangnya 15 minit. Pegang kelopak mata terbuka dan jauh dari bola mata untuk memastikan semua permukaan dibilas dengan bersih. Segera hubungi pakar oftalmologi.
Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
- Pertolongan cemas selepas pengingesan
First-aid measures after ingestion : Pengingesan tidak dianggap sebagai jalan pendedahan yang berpotensi
Ingestion is not considered a potential route of exposure.

4.2 Gejala dan kesan yang paling penting, baik yang akut mahupun yang tertangguh

Most important symptoms and effects, both acute and delayed

Tiada maklumat tambahan tersedia
No additional information available

4.3 Petunjuk untuk mendapatkan rawatan perubatan segera dan rawatan khas yang diperlukan

Indication of any immediate medical attention and special treatment needed

If breathing is difficult, give oxygen. Obtain medical attention if breathing difficulty persists.

SEKSYEN 5: Langkah-langkah memadam kebakaran

Firefighting measures

5.1 Media pemadam

Extinguishing media

Jenis pemadam yang sesuai

Suitable extinguishing media

Karbon dioksida, Serbuk Kimia kering, Air Spray atau Kabus.

Carbon dioxide, dry chemical powder, water spray or fog.

5.2 Bahaya khas yang timbul daripada bahan atau campuran

Special hazards arising from the substance or mixture

- Bahaya khusus : Pendedahan kepada kebakaran mungkin menyebabkan bekas pecah atau meletup. SANGAT MUDAH TERBAKAR
Specific hazard *Supports combustion. Exposure to fire may cause containers to rupture/explode. EXTREMELY FLAMMABLE GAS.*
- Pembakaran bahaya produk : Gas mudah terbakar. Membentuk campuran letupan dengan udara dan agen pengoksidaan.
Hazardous combustion products *EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.*

5.3 Nasihat untuk anggota bomba

Advice for firefighters

- Kaedah khusus : Pendedahan kepada api boleh menyebabkan bekas pecah/meletup. Sekiranya boleh, hentikan aliran produk. Terus semburkan air dari kedudukan terlindung sehingga bekas tetap sejuk. Jauhkan bekas dari Kawasan kebakaran jika ia dapat dilakukan tanpa risiko.
Specific methods *Exposure to fire may cause containers to rupture/explode. If possible, stop flow of product. Continue water spray from protected position until container stays cool. Move containers away from the fire area if this can be done without risk.*
- Peralatan pelindung khas untuk bomba : Mengasingkan sumber pembakaran dari api. Sembur air berterusan dari kawasan yang dilindungi untuk memastikan kontena sejuk. Gunakan alat pernafasan semasa dalam ruang terkurung.
Special protective equipment for fire fighters *In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 -Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 -Protective clothing for firefighters. Standard -EN 659: Protective gloves for firefighters*
- Arahan memadam kebakaran : Sekiranya berlaku kebakaran: Pindahkan api dari jarak jauh kerana risiko letupan. Gunakan semburan air atau kabut untuk menyejukkan bekas yang terdedah. Berhati-hatilah semasa melawan api kimia.
Firefighting instructions *In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.*

SEKSYEN 6: Langkah-langkah pelepasan tidak sengaja

Accidental release measures

6.1 Langkah-langkah keselamatan berkaitan orang perseorangan

Personal precautions, protective equipment and emergency procedures

- Langkah berjaga-jaga am : Pakai alat pernafasan diri kecuali jika kawasan terbukti selamat.
General measures *Mengosongkan kawasan. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Evacuate area*
- Langkah berjaga-jaga alam sekitar : Cuba tolak pelepasan (menggunakan pernafasan diri radas)
Environmental precautions *Try to stop release*

6.2 Kaedah dan bahan-bahan untuk pembendungan dan pembersihan

Methods and materials for containment and cleaning up

Ventilasikan kawasan dengan teliti dan jangan masuk tanpa peralatan pernafasan melainkan jika ada kawasan telah dinyatakan selamat. Buang isi dan bekas mengikut peraturan tempatan/regional/nasional/ antarabangsa
Ventilate the area carefully and do not enter without breathing apparatus unless there is an area that has been declared safe. Dispose of contents/containers in accordance with local/regional/national/international regulations.

6.3 Rujukan ke bahagian lain

Reference to other sections

Lihat seksyen 8 dan 13.

See also sections 8 and 13

SEKSYEN 7: Pengendalian dan penyimpanan

Handling and storage

7.1 Langkah berjaga-jaga untuk pengendalian yang selamat

Precautions for safe handling

Bahan mesti dikendalikan mengikut prosedur kebersihan dan keselamatan industri yang baik. Hanya orang yang berpengalaman dan diarahkan dengan betul yang boleh mengendalikan gas di bawah tekanan. Pengendali harus memakai pakaian pelindung semasa mengendalikan gas ini. Pertimbangkan alat pelepas tekanan di pemasangan gas. Pastikan sistem gas yang lengkap (atau kerap) diperiksa untuk kebocoran sebelum digunakan. Jangan merokok semasa mengendalikan produk. Elakkan terdedah, dapatkan arahan khas sebelum digunakan. Gunakan hanya peralatan yang ditentukan dengan betul dan sesuai untuk produk ini, tekanan dan suhu bekalannya. Hubungi pembekal gas anda sekiranya ragu-ragu. Jangan menghirup gas. Elakkan pelepasan produk ke atmosfera.

The substance must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Operators should wear protective clothing while handling this gas. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Avoid exposure, obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid release of product into atmosphere.

Safe handling of the gas receptacle

Lindungi silinder dari kerosakan fizikal: jangan seret, gulung, geser atau jatuh. Jangan keluarkan atau mencacatkan label yang diberikan oleh pembekal untuk mengenal pasti kandungan silinder

Protect cylinders from physical damage: do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

7.2 Keadaan yang perlu untuk memastikan penyimpanan selamat, termasuk perhatian kepada sebarang ketidakserasian

Conditions for safe storage, including any incompatibilities

Patuhi semua peraturan dan keperluan setempat berhubung penyimpanan bekas. Bekas tidak boleh disimpan dalam keadaan yang berkemungkinan menggalakkan pengkakisian. Pengawal injap atau penutup bekas sepatutnya dipasang dengan betul. Bekas sepatutnya disimpan dalam keadaan menegak dan diikat dengan betul untuk mencegah daripada terjatuh. Bekas yang disimpan seharusnya diperiksa secara berkala untuk mengetahui keadaannya secara am dan memastikan tiada kebocoran. Simpan bekas pada suhu kurang daripada 50°C di tempat yang mempunyai pengalihan udara yang baik. Simpan bekas di lokasi yang bebas daripada bahaya kebakaran dan jauh dari sumber haba dan pencucuhan. Jauhkan daripada bahan boleh bakar.

Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be

stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

SEKSYEN 8: Kawalan pendedahan dan perlindungan diri

Exposure controls and personal protection

8.1 Parameter kawalan

Control parameters

Methane (74-82-8)	
ACGIH	Not established
USA OSHA	Not established

Ethane (74-84-0)	
ACGIH TLV (United States, 3/2017)	Oxygen depletion [Asphyxiant].

Carbon dioxide (124-38-9)	
ACGIH TLV (United States, 3/2017)	Oxygen depletion [Asphyxiant]. STEL: 30000 ppm 15 minutes TWA: 5000 ppm 8 hours.
OSHA PEL (United States, 6/2016).	TWA: 5000 ppm 8 hours.

Nitrogen (7727-37-9)	
ACGIH TLV (United States, 3/2019)	Oxygen depletion [Asphyxiant].

Propane (74-98-6)	
ACGIH TLV (United States, 3/2019)	Oxygen depletion [Asphyxiant]. Explosive potential.
OSHA PEL (United States, 5/2018)	TWA: 1000 ppm 8 hours.

Iso-butane (75-28-5)	
ACGIH TLV (United States, 3/2017)	STEL: 1000 ppm 15 minutes.

n-Butane (106-97-8)	
ACGIH TLV (United States, 3/2017)	STEL: 1000 ppm 15 minutes.

Iso-pentane (78-78-4)	
ACGIH TLV (United States, 3/2019)	TWA: 1000 ppm 8 hours.
USA OSHA	Not established

n-Pentane (109-66-0)	
ACGIH TLV (United States, 3/2019)	TWA: 1000 ppm 8 hours.
OSHA PEL (United States, 5/2018)	TWA: 1000 ppm 8 hours

neo-Pentane (463-82-1)	
ACGIH TLV (United States, 3/2017)	TWA: 1000 ppm 8 hours.

n-Hexane (110-54-3)	
ACGIH TLV (United States, 3/2019)	Absorbed through skin.
	TWA: 50 ppm 8 hours.
OSHA PEL (United States, 5/2018)	TWA: 500 ppm 8 hours

8.2 Kawalan pendedahan

Exposure controls

Kawalan kejuruteraan yang sesuai <i>Appropriate engineering controls</i>	:	Pastikan pengudaraan udara yang mencukupi. Sistem di bawah tekanan harus diperiksa secara berkala untuk mengetahui kebocoran. Pastikan pendedahan berada di bawah had pendedahan pekerjaan (jika ada). Pengesan gas harus digunakan apabila gas toksik dilepaskan. Pertimbangkan system permit kerja untuk aktiviti pentelenggaraan <i>Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when toxic gases may be released. Consider work permit system e.g. for maintenance activities.</i>
Perlindungan kulit <i>Skin protection</i>	:	Pakai sarung tangan kerja sewaktu mengendalikan bekas gas. Standard EN 388 - Sarung tangan perlindungan terhadap risiko mekanikal. Pakai sarung tangan penebatan sejuk sewaktu memindah isi atau memutuskan sambungan pemindahan. Standard EN 511 - Sarung tangan penebatan sejuk. Pakai kasut keselamatan sewaktu mengendalikan bekas. Pakai kasut keselamatan sewaktu mengendalikan bekas. Standard EN ISO 20345 - Peralatan perlindungan diri - Kasut keselamatan <i>Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.</i>
Perlindungan mata/muka <i>Eye/face protection</i>	:	Pakai gogal apabila memindah isi atau memutuskan sambungan pemindahan. Standard EN 166 - Perlindungan mata peribadi. <i>Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.</i>
Perlindungan saluran pernafasan <i>Respiratory protection</i>	:	Penapis gas juga boleh digunakan jika semua keadaan sekeliling, contohnya, jenis dan kepekatan bahan cemar dan tempoh penggunaan diketahui. Alat pernafasan serba lengkap (SCBA) atau saluran udara tekanan positif dengan topeng hendaklah digunakan dalam atmosfera kekurangan oksigen. <i>Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</i>
Cadangan sarung tangan <i>Glove Recommendations</i>	:	Untuk gas: Pakai sarung tangan tahan kimia yang sesuai. Untuk cecair: Pakai sarung tangan bertebat <i>For the gas: Wear appropriate chemical resistant gloves. For the liquid: Wear insulated gloves.</i>
Kawalan pendedahan alam sekitar <i>Environmental exposure controls</i>	:	Rujuk peraturan tempatan untuk pembatasan pelepasan ke atmosfera <i>Refer to local regulations for restriction of emissions to the atmosphere.</i>

SEKSYEN 9: Ciri- ciri fizikal dan kimia

Physical and chemical properties

9.1 Maklumat mengenai sifat fizikal dan kimia asas

Information on basic physical and chemical properties

Bentuk jirim : Gas

Physical state

Rupa <i>Appearance</i>	:	Gas tidak bewarna <i>Colorless gas</i>
Bau <i>Odor</i>	:	Tidau berbau <i>Odorless</i>
Had bau <i>Odor threshold</i>	:	Tiada data tersedia <i>No data available</i>
pH	:	Tidak berkenaan <i>Not applicable</i>
Kadar penyejatan relatif (butyl acetate=1) <i>Relative evaporation rate (butyl acetate=1)</i>	:	Tidak berkenaan untuk campuran gas <i>Not applicable for gas mixture</i>
Kadar penyejatan relative (ether=1) <i>Relative evaporation rate (ether=1)</i>	:	Tidak berkenaan <i>No applicable</i>
Takat cair <i>Melting point</i>	:	Tiada data tersedia <i>No data available</i>
Titik beku <i>Freezing point</i>	:	Tiada data tersedia <i>No data available</i>
Takat didih <i>Boiling point</i>	:	Tiada data tersedia <i>No data available</i>
Julat cair <i>Flash point</i>	:	Tiada data tersedia <i>No data available</i>
Suhu kritikal <i>Critical temperature</i>	:	Tidak boleh didapati <i>Not available</i>
Suhu swanyalaan <i>Auto-ignition temperature</i>	:	Tidak boleh didapati <i>Not available</i>
Suhu penguraian <i>Decomposition temperature</i>	:	Tidak boleh didapati <i>Not available</i>
Kemudahbakaran (pepejal, gas) <i>Flammability (solid, gas)</i>	:	Gas mudah terbakar <i>Flammable gas</i>
Tekanan wap <i>Vapor pressure</i>	:	Tidak berkenaan <i>Not applicable</i>
Ketumpatan wap relatif pada 20 °C <i>Relative vapor density at 20°C</i>	:	Tiada data tersedia <i>No data available</i>
Ketumpatan relatif <i>Relative density</i>	:	Tiada data tersedia <i>No data available</i>
Ketumpatan <i>Density</i>	:	Tiada data tersedia <i>No data available</i>
Ketumpatan gas relatif <i>Relative gas density</i>	:	Tiada data tersedia <i>No data available</i>
Kelarutan <i>Solubility</i>	:	Tiada data tersedia <i>No data available</i>
Log Pow	:	Tiada data tersedia <i>No data available</i>
Log Kow	:	Tidak berkenaan <i>Not applicable</i>
Kepekatan, kinematic <i>Viscosity, kinematic</i>	:	Tidak berkenaan <i>Not applicable</i>
Kepekatan, dinamik <i>Viscosity, dynamic</i>	:	Tidak berkenaan <i>Not applicable</i>
Ciri-ciri letupan	:	Tidak berkenaan

Explosive properties

Sifat oksida

Oxidizing properties

Had letupan

Explosion limits

Not applicable

: Tiada

None

: Tiada data tersedia

No data available

9.2 Informasi lain

Other Information

Kumpulan gas

Gas group

Maklumat tambahan

Additional information

: Gas termampat.

Compressed gas

: Tiada.

None

SEKSYEN 10: Kestabilan dan kereaktifan

Stability and reactivity

10.1 Kereaktifan

Reactivity

Tiada bahaya kereaktifan selain daripada kesan yang diterangkan dalam subseksyen dibawah

No reactivity hazard other than the effects described in sub-sections below

10.2 Kestabilan kimia

Chemical stability

Stabil di bawah keadaan biasa

Stable under normal conditions

10.3 Kemungkinan tindak balas berbahaya

Possibility of hazardous reactions

Tiada maklumat tersedia

No information available

10.4 Keadaan yang perlu dielakkan

Conditions to avoid

Tiada maklumat tersedia

No information available

10.5 Bahan tidak serasi

Incompatible materials

Tiada maklumat tersedia

No information available

10.6 Produk penguraian yang berbahaya

Hazardous decomposition products

Dalam keadaan penyimpanan dan penggunaan biasa, produk penguraian berbahaya tidak boleh dihasilkan

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SEKSYEN 11: Maklumat toksikologi

Toxicological information

11.1 Maklumat tentang kesan ketoksikan

Information on toxicological effects

Ketoksikan akut

Acute toxicity

N-butane (106-97-8)	
LC50 inhalation vapor (Rat)	658000 mg/m ³ 4 hours
Iso-butane (75-28-5)	
LC50 inhalation vapor (Rat)	658000 mg/m ³ 4 hours
Iso-pentane (78-78-4)	
LC50 inhalation vapor (Rat)	280000 mg/m ³ 4 hours
n-Pentane (109-66-0)	
LC50 Inhalation Vapor (Rat)	364 g/m ³ 4 hours
n-Hexane (110-54-3)	
LC50 Inhalation Gas (Rat)	48000 ppm 4 hours

Kakisan/kerengsaan kulit

Skin corrosion/irritation

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Kerosakan/radang mata yang serius

Serious eye damage/eye irritation

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Saluran pernafasan atau kulit menjadi peka

Respiratory or skin sensitisation

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Sel kuman mutagen

Germ cell mutagenicity

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Karsinogen

Carcinogenicity

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Ketoksikan organ sasaran khusus (pendedahan sekali)

Specific target organ toxicity - single exposure

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Ketoksikan organ sasaran khusus (pendedahan berulang kali)

Specific target organ toxicity - repeated exposure

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

Bahaya resapan

Aspiration hazard

Tiada kesan yang diketahui daripada produk ini

No known effects from this product

SEKSYEN 12: Maklumat ekologi**Ecological information****12.1 Ketoksikan****Toxicity**

Tiada kerosakan ekologi yang diketahui disebabkan oleh produk ini.

There is no known ecological damage caused by this product.

n-Hexane (110-54-3)	
LC50 Fish 1	2.54 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
n-Pentane (109-66-0)	
LC50 Fish 1	4.26 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	2.7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ECr50 Algae 1	11.59 mg/l (Exposure time: 96 h - Species: Selenastrum capricornutum)

12.2 Kegigihan dan kemorosotan**Persistence and degradability**

Tiada maklumat tersedia untuk campuran ini

No information available for the mixture

12.3 Keupayaan/potensi pengumpulan bio**Bioaccumulative potential**

Methane (74-82-8)	
Log Pow	1.09
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
Nitrogen (7727-37-9)	
Log Pow	0.67
Log Kow	Not applicable
Bioaccumulative potential	No ecological damage caused by this product.
Ethane (74-84-0)	
Log Pow	1.09
Log Kow	Not applicable
Bioaccumulative potential	Not expected to bioaccumulate due to the low Pow (log Pow < 4).
Propane (74-98-6)	
Log Pow	1.09
Log Kow	Not applicable.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
Carbon dioxide (124-38-9)	
Log Pow	0.83
Bioaccumulative potential	No ecological damage caused by this product
n-Butane (106-97-8)	
Log Pow	2.89
Bioaccumulative potential	Not expected to bioaccumulate due to the low Pow (log Pow < 4).
Iso-butane (75-28-5)	
Log Pow	2.89
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
Iso-pentane (78-78-4)	
Log Pow	3.00

Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
n-Pentane (109-66-0)	
Log Pow	3.45
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
Neo-pentane (463-82-1)	
Log Pow	3.11
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Pow (log Pow < 4).
n-hexane (110-54-3)	
Log Pow	4.00
Bioaccumulative potential	Expected to bioaccumulate due to the high log Pow.

12.4 Pergerakan di dalam tanah

Mobility in soil

Metana: Ekologi-tanah, kerana kemeruapannya yang tinggi, produk tersebut tidak mungkin menyebabkan pencemaran tanah atau air.

Methane: Ecology-soil, because of its high volatility, the product is unlikely to cause ground or water pollution.

Nitrogen: Tiada kerosakan ekologi yang disebabkan oleh produk ini

Nitrogen: No ecological damage caused by this product

Etana, Propana: Kerana turun naik yang tinggi, produk tidak mungkin menyebabkan pencemaran tanah atau air.

Ethane, Propane: Because of high volatility, the product is unlikely to cause ground or water pollution.

Karbon dioksida: Tiada kerosakan ekologi yang disebabkan oleh produk ini

Carbon dioxide: No ecological damage caused by this product

12.5 Kesan-kesan berbahaya yang lain

Other adverse effects

Tiada.

Not available

SEKSYEN 13: Maklumat pelupusan

Disposal information

13.1 Kaedah pelupusan

Disposal methods

Kaedah pelupusan hendaklah mematuhi undang-undang alam sekitar kebangsaan dan peraturan- peraturannya. Jangan buang ke tempat dimana pengumpulan gas boleh membahayakan.

Dispose in accordance with all applicable regulations.

Do not discharge into any place where its accumulation could be dangerous

SYEKSEN 14: Maklumat pengangkutan

Transportation information

Sesuai dengan ADR/RID:

In accordance with ADR/RID:

UN-No. (ADR/RID) : UN1954

Nama penghantaran UN yang betul (ADR/RID) : GAS MAMPAT, MUDAH TERBAKAR, N.O.S.

UN Proper Shipping Name (ADR/RID) (Metana, Karbon dioksida/Etana/Isobutana/n-Butana)/(Karbon dioksida/Etana/Isobutana/n-Butana, Metana)*
COMPRESSED GAS, FLAMMABLE, N.O.S.
(Methane, Carbon dioxide/Ethane/Isobutane/n-Butane)/(Carbon dioxide/Ethane/Isobutane/n-

Kelas bahaya (ADR/RID) <i>Hazard class (ADR/RID)</i> Pelabelan <i>Labelling</i>	<i>Butane,Methane)*</i> *Kompaun dengan kepekatan tertinggi mesti didahulukan bersama dengan kepekatan kedua tertinggi di antara campuran. <i>*The compound with highest concentration must be put first along with the second highest concentration among the mixture.</i> : 2.1, Gas mudah terbakar <i>2.1, Flammable Gas</i> : 
Pengangkutan melalui laut <i>Transport by sea</i> UN-No. (IMDG) Nama penghantaran UN yang betul (IMDG) <i>UN Proper Shipping Name (IMDG)</i>	: UN1954 : GAS MAMPAT, MUDAH TERBAKAR, N.O.S. (Metana, Karbon dioksida/Etana/Isobutana/n-Butana)/(Karbon dioksida/Etana/Isobutana/n-Butana, Metana)* <i>COMPRESSED GAS, FLAMMABLE, N.O.S.</i> <i>(Methane, Carbon dioxide/Ethane/Isobutane/n-Butane)/(Carbon dioxide/Ethane/Isobutane/n-Butane,Methane)*</i> *Kompaun dengan kepekatan tertinggi mesti didahulukan bersama dengan kepekatan kedua tertinggi di antara campuran. <i>*The compound with highest concentration must be put first along with the second highest concentration among the mixture.</i>
Kelas Bahaya (IMDG) <i>Hazard Class (IMDG)</i>	: 2.1, Gas mudah terbakar <i>2.1, Flammable Gas</i>
Pengangkutan melalui udara <i>Air transport</i> UN-No. (IATA) Nama penghantaran UN yang betul (IATA) <i>UN Proper Shipping Name (IATA)</i>	: UN1954 : GAS MAMPAT, MUDAH TERBAKAR, N.O.S. (Metana, Karbon dioksida/Etana/Isobutana/n-Butana)/(Karbon dioksida/Etana/Isobutana/n-Butana, Metana)* <i>COMPRESSED GAS, FLAMMABLE, N.O.S.</i> <i>(Methane, Carbon dioxide/Ethane/Isobutane/n-Butane)/(Carbon dioxide/Ethane/Isobutane/n-Butane,Methane)*</i> *Kompaun dengan kepekatan tertinggi mesti didahulukan bersama dengan kepekatan kedua tertinggi di antara campuran. <i>*The compound with highest concentration must be put first along with the second highest concentration among the mixture.</i>
Kelas Bahaya (IATA) <i>Hazard Class (IATA)</i>	: 2.1, Gas mudah terbakar <i>2.1, Flammable Gas</i>
Maklumat tambahan (ADR/RID/IMDG/IATA)	

Additional Information (ADR/RID//IMDG/IATA)

Kumpulan pembungkusan	: Tidak berkenaan
<i>Packing group</i>	<i>Not applicable</i>
Bahaya terhadap alam sekitar	Tiada
<i>Environmental hazards</i>	<i>None</i>
Pengangkutan secara pukal mengikut Lampiran II Marpol dan kod IBC	: Tidak berkenaan
<i>Transport in bulk according to Annex II of Marpol and the IBC code</i>	<i>Not applicable</i>
Langkah pengangkutan berjaga jaga	: Memastikan pemandu memahami potensi bahaya dan tahu langkah yang perlu dilakukan sekiranya berlaku kemalangan atau kecemasan. Bercagar bekas produk sebelum diangkut. Pastikan injap silinder ditutup dan tiada kebocoran. Pastikan pengudaraan yang mencukupi.
<i>Special transport precautions</i>	<i>Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:-Ensure there is adequate ventilation.-Ensure that containers are firmly secured.-Ensure cylinder valve is closed and not leaking.-Ensure valve outlet cap nut or plug (where provided) is correctly fitted.-Ensure valve protection device (where provided) is correctly fitted.</i>

SEKSYEN 15: Maklumat pengawalseliaan

Regulatory information

15.1 Peraturan Antarabangsa

Memastikan semua peraturan nasional/ tempatan dipatuhi.

Ensure all national/local regulations are observed.

SEKSYEN 16: Lain-lain maklumat

Other information

Apabila anda mencampur dua atau lebih bahan kimia, anda boleh mencipta bahaya tambahan dan tidak dijangka. Mendapatkan dan menilai maklumat keselamatan bagi setiap komponen sebelum anda menghasilkan campuran. Rujuk pakar kebersihan industri atau orang terlatih yang lain apabila anda menilai produk akhir. Sebelum menggunakan sebarang plastik, sahkan keserasian mereka dengan produk ini.

Pengguna produk ini hendaklah mempelajari SDS ini dan menyedari bahaya produk dan maklumat keselamatan. Untuk menggalakkan penggunaan produk ini dengan selamat, pengguna harus (1) memberitahu pekerja, ejen, dan kontraktor maklumat dalam SDS ini dan maklumat bahaya dan keselamatan produk lain yang diketahui, (2) memberikan maklumat ini kepada setiap pembeli produk, dan (3) minta setiap pembeli memberitahu pekerja dan pelanggan tentang bahaya produk dan maklumat keselamatan.

When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Users of this product are to study this SDS and become aware of the product hazards and safety information. To

promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

Maklumat Lanjut

Further information

Hakcipta 2023 Lesen Chroma Gas Sdn Bhd yang diberikan untuk membuat salinan kertas tanpa had untuk kegunaan dalaman sahaja. Maklumat di atas dipercayai betul tetapi tidak bermaksud untuk menjadi semua inklusif dan hanya akan digunakan sebagai panduan. Maklumat dalam dokumen ini adalah berdasarkan pada pengetahuan terkini dan boleh digunakan untuk produk berkenaan dengan langkah berjaga-jaga keselamatan yang sesuai. Ia tidak mewakili apa-apa jaminan terhadap sifat produk tersebut. Chroma Gas Sdn Bhd tidak akan dipertanggungjawabkan untuk apa-apa kerosakan yang disebabkan oleh pengendalian atau daripada hubungan dengan produk di atas.

Copyright 2023 Chroma Gas Sdn Bhd License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Chroma Gas Sdn Bhd shall not be held liable for any damage resulting from handling or from contact with the above product.
